



# kingpiN™

## AGV Motion Regulator and Control

### Accelerating Autonomous Mobile Robot / AGV Development

kingpiN™ - A versatile, industry proven controller specifically designed for robotic / autonomous vehicle control applications. Supports all vehicle drive configurations and forms the central component of a scalable Guidance Navigation, and Control solution.

A smart controller specifically designed and built for robotic vehicle applications. A built-in pedigree that accelerates robotic vehicle development without compromising the user's ability to stay in control of vehicle functionality.

Ready to use with a range of navigation/localisation technologies and third-party traction and steer motor drives. A truly modular solution, allowing user choice and easy adaptation to application needs.

kingpiN™ can provide position by using the optional onboard and external navigator / localiser solution that can determine a vehicles position by:

- Natural feature/contour
- Surface-based reference marks e.g. RFID, lines, barcodes
- Reflector constellation
- GPS/GNSS

### Applications

Used in vehicle applications including: Mobile Conveyors, Tow Tractors, Pedestrian Tugs, Submarine AGV, Pallet Trucks, Fork Lift Trucks, Floor Cleaning Machines, Autonomous Mobile Pick Carts/Robots, Surface Printing Vehicles.

### Benefits

Reduced development cost, reduced time to market, access to proven state of the art guidance and navigation technologies.



# Controller Specification

<b>Drive Configurations supported</b>	
Differential	Quad
Tricycle	User Specific e.g. Quad differential drive
<b>Options</b>	
Onboard Navigators:	
SCENE	<ul style="list-style-type: none"> <li>Natural Feature Navigation</li> <li>GPS Additional Receiver Required</li> <li>GNSS</li> </ul>
<b>CPU</b>	
	Intel® Celeron® Processor J1900 (2M Cache, Up to 2.42 GHz SoC, 10W TDP)
<b>BIOS</b>	
	AMI 64 Mbit SPI BIOS
<b>Memory</b>	
	1x DDR3L 204-pin SO-DIMM, up to 8GB (1066/1333MHz, un-buffered)
<b>Storage</b>	
1 x mSATA for full-size mini-PCIe socket	1 x 2.5" SATA 2.0, 1x mSATA (Shared by 1x Mini-PCIe socket)
<b>Graphics</b>	
Integrated Intel® HD Graphics	Two Independent Display
<b>Audio</b>	
Realtek® ALC888S	High Definition Audio
<b>I/O Interface</b>	
1x DVI-I Connector, Up to 1920 x 1080	2x GbE LAN Ports (Support Wake On Lan, Teaming, Jumbo Frame, PXE), RJ45
4x RS-232/422/485, Auto Flow Control, DB9	1x USB 3.0 & 3x USB 2.0 (Type-A)
1x Mic-in and 1x Line-out, Phone Jack 3.5mm	1x ATX Power On/Off Switch Button
1x AT/ATX Mode Switch	1x Remote Power On/Off Connector, 2-Pin Terminal Block
	2 x CANbus / CANopen Connection - 9W D-Sub Male Connector
<b>Expansion</b>	
1x CMI Interface for CMI Modules	2x Full-size Mini-PCIe (Supports Wireless & I/O Expansion)
1x SIM Socket	2x Antenna Holes
<b>Diagnostics Ethernet</b>	
Software Upgrade	Remote Software Upgrade and Diagnostics
<b>Electrical</b>	
Operating Voltage	9~48VDC
Power Consumption	Typical 8.3W, Max.15W
<b>Protection</b>	
Reverse Power Input Protection Supported	Over Voltage Protection (OVP) Up to 51V
Over Current Protection (OCP) 120V/ 20A	ESD Protection Air Discharge: 8 kV; Contact Discharge: 4 kV (IEC 61000-4-2)
<b>Other Function</b>	
Instant Reboot Technology (0.2 sec)	Watchdog Timer: Software Programmable Supports 1~255 sec. System Reset
<b>Environmental</b>	
Operating Temp	-25°C to 70°C (SSD) with Air Flow IEC60068-2-1, IEC60068-2-2, IEC60068-2-14
Storage temperatures	-40°C to 85°C with air flow
Shock	50 Grms (With SSD According to IEC 60068-2-27, Half Sine, 11ms Duration)
Relative Humidity:	95% RH @ 40°C (Non-Condensing)
Vibration	Random: 5 Grms (With SSD According to IEC 60068-2-64, 5~500Hz, 1 hr/axis)
<b>Housing</b>	
Dimensions	(W x D x H): 150 x 105 x 56.02 mm
Weight	0.86 kg
<b>External Navigators</b>	
SCENE	BEACON
	SURFACE
<b>2D/3D Laser Scanning Options</b>	
Pepperl & Fuchs R2000	Sick S300/S3000
Omron 0S32C	Hokuyo UAM-05LP-T301/T301C
Others on Request	
<b>Certification</b>	
CE	FCC Class A

*An award-winning pioneer in guidance, navigation and control technologies, Guidance Automation has over 25 years' experience in developing advanced solutions for the global robotic vehicle market and has thousands of systems in service.*

*Our aim is to consistently meet our clients' needs by offering automated guided vehicle technologies which serve the market need and improve operational performance and efficiency.*

*We are proud to have enabled our clients to automate robotic vehicles, fork lift trucks, floor cleaning equipment and all types of mobile moving systems. These solutions have been applied in a broad range of autonomous transport applications such as airports, warehousing, healthcare, production, bottling plants, printing, retail, marine and more.*

*We are committed to the continuous advancement of innovative and optimal vehicle automation.*



Unit 2 Meridian South  
Meridian Business Park  
Leicester LE19 1WY  
United Kingdom

Tel: +44 116 243 6250

[enquiries@guidanceautomation.com](mailto:enquiries@guidanceautomation.com)  
[guidanceautomation.com](http://guidanceautomation.com)



**Matthews**<sup>TM</sup>  
AUTOMATION SOLUTIONS

Guidance Automation is a (MATW) Matthews International company  
© Guidance Automation. All rights reserved.